

80mm Desktop Receipt Printer

XTKP-607UL



- 1.Support multiple languages.
- 2.Top-notch design, very good texture.
- 3.Support cash drawer command and pos machine connection
- 4.Low-power waste, low-run cost.
- 5.Low cost and high-quality thermal printing.
- 6.Support different density bitmap graphics printing.
- 7.High-speed printing using embedded soft font for all interfaces.
- 8.Easy paper-roll installation, Easy maintenance and rational structure.
- 9.Optional interface: USB/ USB+LAN/ USB+Bluetooth/USB+WIFI.
- 10.Characters can be amplified,printed in bold optionally,and line spacing printing can be adjusted.
- 11.Compatible with ESC/POS print instruction set, optional columns and font(adjusted by DIP switch).
- 12.Can be widely used in manufacturing & warehouse logistic industry, healthcare, parcel post, office, studio, retail etc.

Model: AI-80D 80mm Desktop Receipt Printer	
Printing	
Printing Method	Line thermal printer
Printing Command	ESC/POS compatible with order sets
Printing Width	72mm
Printing Speed	220mm/s
Printing Resolution	8 dots/mm, 576 dots/line
Character	
Character Set	ANK,GB18030(Chinese)
Print Font	ANK: 12 x24 ,9x17 Chinese: 24 x 24
Character Per Line	42
Text and Graphic Support	English,Figure,Symbol,Chinese,Graph,Curve,Icon,Pre-stored,Barcode(UPC-A,UPC-E,EAN-13,EAN-8,CODE39,CODE93, CODE128,CODEBAR,ITF25) QR code,PDF417
Self-Check	Driver Check / Button Check
Black Mark Test	Support
Paper	
Paper Type	Thermal paper
Paper Width	79.5±0.5mm
Paper Roll Diameter	Max: 80.0mm
Roll Core Inner Diameter	13mm(min.)
Paper Thickness	0.06 to 0.08mm
Paper Feeding	Easy paper loading
Paper Cut	With auto cutter
Cutter Life	1,000,000 cuts
Specification	
Life Cycle Time	100km(printing density under 12.5%)/100 million pulses
Drawer Port	1 Port
Interface	USB/LAN/ Bluetooth/WIFI
Power Supply (Adapter)	AC100 ~240V(± 10%) DC 24V, 2A
Dimension	138*167*120mm
Weight	826g (only printer)
Operation Environment	Temperature -20°C~60°C ; Humidity 20%~85%
Storage Environment	Temperature -20°C~70°C ; Humidity 5%~95%
Warranty	2 Years
Certificate	CE FCC RoHS IP54

Packing information:

- Standard List: Printer + Power Adapter + USB Cable + Thermal paper
+Manual
- Box Size: 20.5*18.6*14cm Box GW:1KG
- Carton Size: 61.4*38.8*29.8cm Carton GW:14KG
- 12pcs/ carton